

## SANIPOWER TP30V

Domestic / Commercial sewage disposal unit

### APPLICATION

Sanipower is suitable for pumping sewage and waste water from toilets, hand basins, showers and from rooms which are below the sewer level, or in commercial applications e.g. kitchens, bars and bathrooms.

### DESIGN FEATURES

- Odour and gas tight composite plastic collecting tank
- Single stage centrifugal pump with horizontal discharge
- Vortex impeller with spherical clearance of 30mm
- Fully submersible, pressure tight electric motor
- Stainless steel rotor shaft, pre-lubricated bearings
- Combination of mechanical seal (silicon carbide) and lip seal in oil chamber
- Pneumatic level control with pressure switch
- Electronic control box motor over run period, over load protection, temperature control of winding and automatic motor restart



### TECHNICAL DATA

Input / Output (kW)	1.6 / 1.2	Total Volume	11 litres
Voltage 50Hz (V)	230-240 / 1 phase	Inlet size	DN100 (other sizes on request)
Speed (rpm)	2900	Air Vent Size	DN50
Nominal Current (A)	7.5	Discharge Size	50mm
Weight (kg)	32	Dimensions (mm)	L490 x W390 x H390
Tank Inlet Height	180mm	50mm Non Return	Supplied (3205)

### Pump Performance

