

## FULL FLOW SWING CHECK NON-RETURN VALVES

Solvent or compression fittings


### APPLICATION

Use in irrigation systems, preventing backflow of corrosive materials in waste water lines, sump pump disposal lines, sewage lift stations or ejector systems.

Use also where minimum head loss or flow resistance is required. Swimming pools, hot tubs or spa applications. Every pump system should have one to stop reverse flow and the risk of pump cycling.

### DESIGN FEATURES

- Silent and reliable
- Full flow design
- No metallic parts, corrosion resistant
- Pressure rated 125psi at 22°C
- Can be installed vertically or horizontally
- Very low head loss due to full clearance
- Compression fittings facilitate easy removal for servicing
- Compression ends can be used as union connections
- PVC weighted and shielded flapper design for low pressure seal



Type 1520

### TECHNICAL DATA (PVC COMPRESSION FITTINGS)

Part No	Type	Size	Length
1500-12	1500	32MM	191MM
1500-15	1500	40MM	191MM
1500-20	1500	50MM	248MM

### TECHNICAL DATA (PVC SOLVENT SLIP CONNECTIONS)

Part No	Type	Size	Length
1520-10	1520	25MM	89MM
1520-12	1520	32MM	134MM
1520-15	1520	40MM	146MM
1520-20	1520	50MM	153MM
1520-40	1520	100MM	245MM