

## Pump Chamber 250 Litre WP250

Domestic/Commercial packaged pump station

### APPLICATION

Wallace WP250 is designed as a secondary unit for domestic applications where a dwelling is below conventional council sewer line and a storage type pump station is required with limited space availability

### DESIGN FEATURES

- Moulded PE tank has compact overall size of 710mm diametre X 780mm (Overall height Incl lid 870mm) with approximate volume of 250ltr
- Compact design can be installed in confined space.
- Unit can be installed Above-Ground or Under-Ground.
- Gland design allows easy access and removal of separate float switches(if supplied) without disturbing pump and piping.
- Package supplied complete with selected Pump.
- Some pump models are with built in float for On/Off operation, however some pump models not having built in float will be supplied with separate float and control panel.
- Control panel **MUST** be installed in weatherproof location.
- Package can be supplied with High Level Alarm System with or without auto water shutoff via solenoid valves. Alarm panel **MUST** be installed in weatherproof location.
- Non Return Valve, Isolating valve and union supplied assembled with 100mm PVC inlet and 50mm PVC outlet



### TECHNICAL DATA

Tank Volume (Litres)	250	Alarm (Type)	Pump Dependant
Dimensions (mm)	710Ø x 780H	Inlet	100mm UPVC
Total Weight (Kg)	30	Discharge	50mm PVC class D
Pump (Type)	Application Specific	Valves	50mm non return & isolating

Pump Performance Based on W-750SK

